



ProLite E2773HS

The ProLite E2773HS LED-backlit 27" monitor features a stunning 1 ms response time and a FHD (1920x1080) resolution. The high brightness and contrast offer the user clear and vivid images, and the HDMI, DVI and VGA connections ensure compatibility across a range of devices including games consoles and workstations. The X-Res Technology feature helps to deliver best quality pictures even if the source is not perfect, like movies made with mobile device.

DISPLAY CHARACTERISTICS

Diagonal	27"
Panel	TN
Display area h x w	336.3 x 597.9 mm; 13.2" x 23.5"
Response time	1 ms
Contrast	1 200 : 1 typical
Contrast	5 000 000 : 1 ACR
Brightness	300 cd/m ² typical
Viewing zone	horizontal/vertical: 170° / 160°; right/left: 85° / 85°; up/down: 80° / 80°
Display colour	16.7 million
Pixel pitch h x v	0.311 x 0.311 mm
Native resolution	Full HD 1080p, 1920 x 1080 (2.1 megapixel)
Horizontal sync	24 - 82 KHz
Vertical sync	55 - 76 Hz
Synchronization	Separate Sync
Aspect ratio	16 : 9

POWER MANAGEMENT

Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	29 W typical; max. 0.5 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®

DIMENSIONS & WEIGHT

Dimensions w x h x d	647 x 454.5 x 239 mm
Weight	5.3 kg

INTERFACES & CONNECTORS

Analog input connector	VGA (D-Sub)
Digital input connector	DVI-D, HDMI
HDCP	yes
Output connector	headphone socket
	D-Sub, DVI-D, HDMI

SPECIAL FEATURES

Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Plug & Play	VESA DDC2B™
Controls	Via OSD in 8 languages (EN, DE, FR, NL, PL, Chinese, JP, RU) and 5 front controls (Power, Select/ Input select, Scroll up/ X-Res Technology, Scroll down/ i-Style Colour, Menu)
User controls	auto adjust, picture adjust (contrast, brightness, ACR, ECO, OD, X-Res Technology), input select, audio adjust (volume, mute, HDMI audio), colour adjust (information, manual image adjust (clock, H/V position, phase, sharpness, video mode adjust), setup menu (language, OSD position, OSD time out, OSD background, opening logo, LED), memory recall
Speakers	2 x 2 W (Stereo)
Anti-theft-device	Kensington-lock™ prepared
Safety	TÜV-Bauart, PSE, CE, VCCI-B, CU
Tilt angle	20° up; ° down
VESA mounting	100 x 100 mm
Colour	Black

ACCESSORIES

Driver	Windows 95 / 98 / 2000 / ME / XP / Vista/ 7 / 8
Included accessories	power cable, VGA (D-Sub) cable, DVI-D cable, audio cable, stand, cable holder, quick start guide, safety guide