Fujitsu recommends Windows® 7.



Data Sheet Fujitsu LIFEBOOK E751 Notebook

The Mobile Top Performer

The simple philosophy behind Fujitsu LIFEBOOK E751: only the best is good enough. State-of-the-art Intel® technology ensures best performance. This 39.6 cm (15.6-inch) notebook supports HD or HD+ display with LED backlight. With features like fingerprint and Fujitsu's Advanced Theft Protection (ATP) your notebook is secured from any data theft.

More than enough performance

Maximum productivity even for the most demanding of applications thanks to state-of-the-art technology.

- 2nd generation Intel® Core™ i3, i5 or i7 processor, optional Intel® vPro™ technology, Intel® integrated graphics
- Optional 0-Watt AC Adapter guarantees that the notebook does not consume electricity when switched off



Effective working even for the most demanding of users in all situations.

- 39.6 cm (15.6-inch) HD or HD+ display, modular bay, optional second hard disk drive
- Anytime USB Charge to charge phones/media devices even when the system is turned off

Maximum connectivity

Be available wherever you are; wireless connectivity anytime anywhere, even if there is no hotspot nearby.

Integrated DisplayPort, eSATA, serial port, optional USB 3.0, optional embedded 3G/UMTS, WLAN and Bluetooth®

Maximum security

Protect your company data against unauthorized third-party access.

 Computrace® enabled BIOS and Advanced Theft Protection, integrated SmartCard slot, optional fingerprint sensor, TPM module and SMARTACCESS

Great flexibility

The family concept offers same design and accessory components for LIFEBOOK E751 and E781 as well as for LIFEBOOK S751 and S781.

Same industrial design, bit image, BIOS and accessories such as port replicator, power supply unit, keyboard and modular bay for optical drive, second battery and second hard disk drive































Components

Processor	Intel® Core™ i7-2640M processor (2.8 GHz, 4 MB)					
	Intel® Core™ i5-2430M processor (2.4 GHz, 3 MB) *					
	Intel® Core™ i5-2410M processor (2.3 GHz, 3 MB) *					
	Intel® Core™ i3-2330M processor (2.2 GHz, 3 MB) *					
	Intel® Core™ i3-2310M processor (2.1 GHz, 3 MB) *					
	Intel® Core™ i7-2620M processor (2.70 GHz, 4 MB)					
	Intel® Core™ i5-2520M processor (2.50 GHz, 3 MB)					
	Intel® Celeron® processor B810 (1.6 GHz, 2 MB)					
	*Processor only for retail, SMB, education and government					
Operating system						
Operating system	Genuine Windows® 7 Professional 64-bit					
	Genuine Windows® 7 Home Premium 64-bit					
	Genuine Windows® 7 Home Basic (EM) 64-bit					
Operating system compatible	Genuine Windows® XP Professional					
	Genuine Windows Vista® Business 32-bit					
Operating system notes	Driver support for Microsoft® Windows® XP Professional					
	Buy Microsoft® Office 2010 to use the full-featured Office software on this PC.					
Memory modules	2 GB (1 module(s) 2 GB) DDR3, 1333 MHz, PC3-10600, SO DIMM					
	4 GB (1 module(s) 4 GB) DDR3, 1333 MHz, PC3-10600, SO DIMM					
Base unit memory	LIFEBOOK E751 15.6-inch					
	(with number block) vPro vPro (with number block)					
Supported capacity RAM (max.)	8 GB					
Memory slots total	2					
Memory slot type	DIMM (DDR3)					
Memory notes	DDR3 - 1333 MHz					
Hard disk drives (internal)	SSD SATA, 128 GB, 2.5-inch					
	SATA, 7200 rpm, 500 GB, 2.5-inch, S.M.A.R.T.					
	SATA, 7200 rpm, 320 GB, 2.5-inch, S.M.A.R.T.					
	SATA, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T.					
	SATA, 5400 rpm, 320 GB, 2.5-inch, S.M.A.R.T.					
	SATA, 5400 rpm, 320 GB, 2.5-inch, S.M.A.R.T.					
	SATA, 5400 rpm, 160 GB, 2.5-inch, S.M.A.R.T.					
	FDE, 5400 rpm, 320 GB, 2.5-inch, S.M.A.R.T.					
Hard disk notes	ShockSensor for HDD shock protection					
riald disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.					
	Accessible capacity may vary, also depending on used software.					
	Up to 18 GB of HDD space is reserved for system recovery					
WLAN (optional)	Atheros Minicard b/g/n					
(°F /	Intel® Centrino® 6205 802.11 a/b/g/n					
Wireless technologies						
Antennas	2 dual band antennas; 1 Bluetooth antenna optional, 2 UMTS antennas optional					
WLAN notes	Import and usage according to country-specific regulations.					
WiDi support	Yes (with Intel W-LAN)					
3G/UMTS (optional)	Sierra Wireless Gobi 3000 (UMTS downlink speed 14.4 Mbit/s, UMTS uplink speed 5.76 Mbit/s)					
Bluetooth (optional)	Bluetooth 3.0					

Page 2 / 7 http://ts.fujitsu.com/mobile

Display	39.6 cm (15.6-inch) LED ha	acklight, (HD+), Anti-glare dis	play compound 1600 v 900 r	ival 300:1 220 cd/m	
Display		acklight, (HD), Anti-glare disp	1 1 1		
Modular bay options	2nd battery				
	2nd hard disk drive				
	Blu-ray Disc™ Triple Writer				
	DVD Super Multi				
	Weight saver				
	,				
Base unit	LIFEBOOK E751 15.6-inch	LIFEBOOK E751 15.6-inch (with number block)	LIFEBOOK E751 15.6-inch vPro	LIFEBOOK E751 15.6-inch vPro (with number block)	
General system information					
Chipset	Intel® HM65		Intel® QM67		
Chipset notes			supports iAMT 7.0, Intel® vPro™ requires Core i5-25xx / processor, Intel W-LAN & TPM module		
BIOS features	BIOS based on Phoenix Trus	BIOS based on Phoenix TrustedCore Notebook			
Graphics					
TFT resolution (DisplayPort)	up to 2560 x 1600				
TFT resolution (VGA)	up to 1920 x 1200				
TFT resolution (DVI on Port Replicator)	up to 1920 x 1200				
Graphics brand name	Intel® HD Graphics				
Graphics features	DualView				
Graphics notes	Shared memory depending	on main memory size and op	erating system		
Interfaces					
Memory card slots	1 (SD/MS/MSPro)	1 (SD/MS/MSPro)	1 (SD/MS/MSPro)	1 (SD/MS/MSPro)	
ExpressCard slots	1 (34 / 54 mm supported)	1 (34 / 54 mm supported)	1 (34 / 54 mm supported)	1 (34 / 54 mm supported)	
SmartCard slot	1	1	1	1	
SIM card slot	1 (usable only with 3G/ UMTS)	1 (usable only with 3G/ UMTS)	1 (usable only with 3G/ UMTS)	1 (usable only with 3G/ UMTS)	
Modem (RJ-11)	1 (optional)	1 (optional)	1 (optional)	1 (optional)	
eSATA & USB combo	1	1	1	1	
USB 3.0 total			1	1	
USB 2.0 total	4 (1x with Anytime USB Charge functionality)	4 (1x with Anytime USB Charge functionality)	3 (1x with Anytime USB Charge functionality)	3 (1x with Anytime USB Charge functionality)	
Serial (RS-232)	1	1	1	1	
VGA	1	1	1	1	
DisplayPort	1	1	1	1	
Ethernet (RJ-45)	1	1	1	1	
DC-in	1	1	1	1	
Audio: line-in / microphone	1	1	1	1	
Audio: line-out / headphone	1	1	1	1	
Internal microphones	as option	as option	as option	as option	
Docking connector for Port Replicator	1	1	1	1	
Kensington Lock support	1	1	1	1	
Wired communication					
Modem type	Optional: 56 K V.92 modem	MDC1.5			
LAN	Built-in 10/100/1000 MBit/s	1 1 10 03570 1/	Built-in 10/100/1000 MBit/s	1 . 10 03570 144	

Page 3 / 7 http://ts.fujitsu.com/mobile

Spill-resistant kephoard with Spill-resistant kephoard keys: Annual Residual keys Spill-resistant keyboard keys: Annual Residual keys: An	Keyboard and pointing devices					
85, kepboard pitch: 19 mm, 166, Kepboard pitch: 19 mm, Kepboard stroke: 2,7 mm mm, Kep		Spill-resistant keyboard	•	Spill-resistant keyboard		
Optional- Fingerprint sensor Optional Sensor		85, Keyboard pitch: 19 mm,	106, Keyboard pitch: 19 mm, Keyboard stroke: 2.7	85, Keyboard pitch: 19 mm,	106, Keyboard pitch: 19 mm, Keyboard stroke: 2.7	
Audio toype Audio codec Realrek ALC769 Audio codec Audio codec Audio codec Sereros opeakers Camera Optional: Bull-in webcam, 1.3 megapixel Power Supply AC Adapter 19 V / 80 W (4, 22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 0-Watt AC Adapter technology 19 V / 80 W (4, 22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 5tandard Adapter 1st battery options Li-lon battery 6-rell, 5600 or 5800 mAh, 63 Wh Li-lon battery 6-rell, 5600 mAh 67 Wh Znd battery (optional) Li-lon battery 6-rell, 5600 mAh, 67 Wh Runtime 1st battery up to 10 h Buttery foreity 6-rell, 5800 mAh, 41 Wh Runtime 1st + 2nd battery up to 17 h Battery foreity 6-rell, 5800 mAh, 180 mAh, 180 mAh Battery horizon Battery foreity 6-rell, 5800 mAh, 180 mAh Battery horizon Battery foreity 6-rell, 5800 mAh, 180 mAh Battery foreity 6-rell, 5800 mAh		Optional: Fingerprint sensor Optional: TouchStick	two mouse buttons			
Audio toype Audio codec Realrek ALC769 Audio codec Audio codec Audio codec Sereros opeakers Camera Optional: Bull-in webcam, 1.3 megapixel Power Supply AC Adapter 19 V / 80 W (4, 22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 0-Watt AC Adapter technology 19 V / 80 W (4, 22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 5tandard Adapter 1st battery options Li-lon battery 6-rell, 5600 or 5800 mAh, 63 Wh Li-lon battery 6-rell, 5600 mAh 67 Wh Znd battery (optional) Li-lon battery 6-rell, 5600 mAh, 67 Wh Runtime 1st battery up to 10 h Buttery foreity 6-rell, 5800 mAh, 41 Wh Runtime 1st + 2nd battery up to 17 h Battery foreity 6-rell, 5800 mAh, 180 mAh, 180 mAh Battery horizon Battery foreity 6-rell, 5800 mAh, 180 mAh Battery horizon Battery foreity 6-rell, 5800 mAh, 180 mAh Battery foreity 6-rell, 5800 mAh	Multimedia					
Audio codec Audio features Stereo Speakers Camera Optional: Built-in webcam, 1.3 megapixel Power supply AC Adapter 19 1/ 80 W (4.22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 0 Watt AC Adapter technology 19 1/ 80 W (4.22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 0 Watt AC Adapter technology 19 1/ 80 W (4.22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 0 Watt AC Adapter technology 19 1/ 80 W (4.22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 0 Watt AC Adapter technology 19 1/ 80 W (4.22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 0 Watt AC Adapter technology 15 th battery options Li-lon battery 6 cell, 6200 mAh, 63 Wh Li-lon battery (6.15, 6200 mAh, 63 Wh Li-lon battery (6.15, 6200 mAh, 63 Wh Runtime 1st battery 10 to 10 Th Runtime 1st + 2nd battery 10 to 10 Th Runtime 1st + 2nd battery 10 to 10 Th Runtime 1st + 2nd battery 10 to 10 Th Runtime 1st + 2nd battery 10 to 10 Th Runtime 1st + 2nd battery 10 to 10 Th Runtime 1st + 2nd battery 10 to 10 Th Runtime 1st + 2nd battery 10 to 10 Th Runtime 1st + 2nd battery 10 to 10 Th Runtime 1st + 2nd battery 10 to 10 Th Runtime 1st + 2nd battery 10 to 10 Th Runtime 1st + 2nd battery 10 to 10 Th Runtime 1st + 2nd battery 10 to 10 Th Runtime 1st + 2nd battery 10 to 10 Th Runtime 1st + 2nd battery 10 to 10 Th Runtime 1st + 2nd battery 10 to 10 Th Runtime 1st + 2nd battery 10 to 10 Th Runtime 1st + 2nd battery 10 to 10 Th Runtime 1st + 2nd battery 10 Th Runtime 1st + 2nd		On board				
Audio features Camea Optional: Bull+in webcam, 1.3 megapixel Power supply AC Adapter 19 V / 80 W (4, 22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 0 Watt AC Adapter technology 19 V / 80 W (4, 22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, Standard Adapter 1st battery options Li-lon battery 6-cell, 5000 or \$800 mAh, 63 Wh Li-lon battery 6-cell, 3,800 mAh, 41 Wh Runtime 1st battery up to 10 h Runtime 1st battery up to 17 h Battery charging time -160 min (5,800 mAh) - 180 min (6,200 mAh) Battery charging time -160 min (5,800 mAh) - 180 min (6,200 mAh) Battery hotes Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery rechange time depends on usage. Rapid charge with 5,800 mAh batteries Dimensions / Weight / Environmental Dimensions / Weight / Environmental Dimensions (W x D x H) Weight notes Incl. weight sweet. Weight may vary depending on actual configuration. Operating mahient temperature 5 - 35°C Operating melative humidity 20 - 80 % Additional software Additional software (preinstalled) Adobe Acrobat Reader Application Panel Display Manager Shocksensor Utility Power Saving Utility Plugitee Network LasyGuide online user documentation Nero Essentials (5) Unrining software) Notron Internet Security (ind. Friewall) on Drivers & Utilities DVD for Microsoft Windows XP Fujitsu Necovery (Hard Disk Based Recovery) Additional software (optional) DeskUpdate Driver management LAMT 7.0 Intel® Pyro™ technology						
Power supply AC Adapter 19 \text{ / 80 W (4,22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 0-Watt AC Adapter technology 19 \text{ / 80 W (4,22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 0-Watt AC Adapter technology 19 \text{ / 80 W (4,22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 0-Watt AC Adapter technology 19 \text{ / 80 W (4,22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 0-Watt AC Adapter technology 19 \text{ / 80 W (4,22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 0-Watt AC Adapter technology 19 \text{ / 80 W (4,22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 0-Watt AC Adapter technology 19 \text{ / 80 W (4,22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 0-Watt AC Adapter technology 19 \text{ / 80 W (4,22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 0-Watt AC Adapter technology 19 \text{ / 80 W (4,22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 0-Watt AC Adapter technology 19 \text{ / 80 W (4,22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 0-Watt AC Adapter technology 19 \text{ / 80 W (4,22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 0-Watt AC Adapter technology 19 \text{ / 80 W (4,22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 0-Watt AC Adapter technology 19 \text{ / 80 W (4,22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 0-Watt AC Adapter technology 19 \text{ / 80 W (4,22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 0-Watt AC Adapter technology 19 \text{ / 80 W (4,22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 0-Watt AC Adapter technology 19 \text{ / 80 W (4,22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 0-Watt AC Adapter technology 19 \text{ / 80 W (4,22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 0-Watt AC Adapter technology 19 \text{ / 80 W (4,22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 0-Watt AC Adapter technology 19 \text{ / 80 W (4,22 A), 100 V (4,40 Pt), 100 Pt} 19 \text{ / 80 W (4,40 Pt), 100 Pt} 19 \text{ / 80 W (4,40 Pt), 100 Pt} 19 \text{ / 80 W (4,40 Pt), 100 Pt} 19 \text{ / 80 W (4,40 Pt), 100 Pt} 19 / 80 W (4,40 Pt), 10						
Power supply AC Adapter 19 V / 80 W (4.22 A), 100 V - 240 V (AC Input) , 50 Hz - 60 Hz, 0-Watt AC Adapter technology 19 V / 80 W (4.22 A), 100 V - 240 V (AC Input) , 50 Hz - 60 Hz, 0-Watt AC Adapter technology 19 V / 80 W (4.22 A), 100 V - 240 V (AC Input) , 50 Hz - 60 Hz, 5tandard Adapter 1st battery options Li-lon battery 6 cell, 5600 or 5800 mAh, 63 Wh Li-lon battery 6 cell, 5600 mAh, 63 Wh Runtime 1st + 2nd battery up to 10 h Runtime 1st - 2nd battery up to 10 h Battery charging time -160 min (5,800 mAh) ~ 180 min (6,200 mAh) Battery charging time -160 min (5,800 mAh) ~ 180 min (6,200 mAh) Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage. Rapid charge with 5,800 mAh batteries Dimensions / Weight / Environmental Dimensions / Weight / Environmental Dimensions (W x D x H) 372 x 245 x 35 mm Weight notes Incl. weight saver. Weight may vary depending on actual configuration. Operating elative humidity 20 ~ 80 % Additional Software Additional Software (preinstalled) Adobe Acrobat Reader Application Panel Display Manager ShockSensor Utility Power Saving Utility Plurigine Network EavyGuide online user documentation Nero Essentials S (burning software) Notton Internet Security (incl. Firewall) on Drivers & Utilities DVD for Microsoft Windows XP Fijitsu Recovery (Hard Disk Based Recovery) DMTS connection manager (optional with UMTS) Manageability Manageability technology DeskUpdate Driver management DeskUpdate Driver management DeskUpdate Driver management DeskUpdate Driver management		•	.3 megapixel			
AC Adapter 19 V / 80 W (4.22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 0-Watt AC Adapter technology 19 V / 80 W (4.22 A), 100 V - 240 V (AC Input), 50 Hz - 60 Hz, 5tandard Adapter 1st battery options Lion battery 6 - cell, 5600 or \$800 mAh, 63 Wh Lion battery 6 cell, 6200 mAh, 67 Wh 2nd battery (optional) Lion battery 6 - cell, 5800 mAh, 41 Wh Runtime 1st battery up to 17 h Battery darging time -160 min (5,800 mAh) ~ 180 min (6,200 mAh) Battery notes Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage. Rapid charge with 5,800 mAh batteries Dimensions / Weight / Environmental Dimensions / Weight / Environmental Dimensions (W x D x H) 372 x 245 x 35 mm Weight notes Incl. weight saver. Weight may vary depending on actual configuration. Operating ambient temperature 2 - 80 % Additional software (preinstalled) Additional Software Additional software (preinstalled) Additional software (preinstalled) Additional software (preinstalled) Additional software (preinstalled) Additional software (prienstalled) Additional software (priented with incl. security (incl. Firewall) on Drivers & Utilities DVD for Microsoft Windows XP Fujitsu Recovery (Hard Disk Based Recovery) Additional software (optional) Diviers & Utilities DVD (DUDVD) UMTS connection manager (optional with UMTS) Manageability Manageability technology BeskUpdate Driver management AMAT 7.0 Intel® vibro™ technology	Power supply		3 1			
19 V / 80 W (4.22 A), 100 V - 240 V (AC Input) ,50 Hz - 60 Hz, Standard Adapter 1st battery options		19 V / 80 W (4.22 A) 100 V -	240 V (AC Input) 50 Hz - 60	Hz. O-Watt AC Adanter technol	loav	
Li-lon battery 6-cell, 5600 or 5800 mAh, 63 Wh Li-lon battery 6-cell, 2600 mAh, 67 Wh 2nd battery (potional) Li-lon battery 6-cell, 28000 mAh, 67 Wh Runtime 1st battery up to 10 h Runtime 1st + 2nd battery up to 17 h Battery charging time -160 min (5,800 mAh) - 180 min (6,200 mAh) Battery notes Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage. Rapid charge with 5,800 mAh batteries Dimensions / Weight / Environmental Dimensions (W x D x H) 372 x 245 x 35 mm Weight 2.5 kg Weight notes Incl. weight saver. Weight may vary depending on actual configuration. Operating ambient temperature Operating alative humidity 20 - 80% Additional Software Additional Software Additional Software Additional software (preinstalled) Power-Saving Utility Power-Saving Utilities DVD for Microsoft Windows XP Easy-Cuide online user documentation Nero Essentials S (burning software) Norton Internet Security (incl. Firewall) on Drivers & Utilities DVD for Microsoft Windows XP Erijtisu Recovery (Hand Disk Based Recovery) Additional software (optional) Drivers & Utilities DVD (DUDVD) UMTS connection manager (optional with UMTS) Manageability Manageability technology DeskUpdate Driver management LiMAT 7.0 Intel® VPto™ technology	, ic riddpict			· · · · · · · · · · · · · · · · · · ·		
Li-lon battery 6-cell, 6-200 mAh, 67 Wh 2nd battery (optional) Li-lon battery 6-cell, 3.800 mAh, 41 Wh Runtime 1st battery Runtime 1st + 2nd battery Up to 17 h Battery charging time Battery notes Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery rechange time depends on usage. Rapid charge with 5,800 mAh batteries Dimensions / Weight / Environmentat Dimensions (W x D x H) 372 x 245 x 35 mm Weight Life with temperature S - 35°C Operating ambient temperature S - 35°C Operating relative humidity Display Manager Additional Software Additional Software (preinstalled) Adobe Acrobat Reader Application Panel Display Manager Shock-Sensor Utility Power Saving Utility Plugfree Network EasyGuide online user documentation Nero Essentials S, Uburning software) Norton Internet Security (Ind. Firewall) on Drivers & Utilities DVD for Microsoft Windows XP Fujitsu Recovery (Hard Disk Based Recovery) Additional software (optional) DeskUpdate Driver management Li-In battery e-Cell management Life W Pro™ technology DeskUpdate Driver management Life X Wh Life T DeskUpdate Driver management Life T DeskUpdate Driver management Life X Wh Life T DeskUpdate Driver management L	1st hattery options	ery options Li-lon battery 6-cell, 5600 or 5800 mAh, 63 Wh				
2nd battery (optional) Li-lon battery 6-cell, 3.800 mAh, 41 Wh Runtime 1st battery up to 10 h Runtime 1st + 2nd battery up to 17 h Battery Arariging time -160 min (5,800 mAh) - 180 min (6,200 mAh) Battery notes Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage. Dimensions / Weight / Environmentat *** Dimensions (W x D x H) 372 x 245 x 35 mm Weight notes Incl. weight saver. Weight may vary depending on actual configuration. Operating ambient temperature 5 - 35°C Operating relative humidity 2 - 80 % Additional Software Adobe Acrobat Reader Application Panel Display Manager ShockSensor Utility Power Saving Utility Plugiree Network Easyfuide online user documentation Nero Essentials S (burning software) Notton Internet Security (incl. Firewall) on Drivers & Utilities DVD for Microsoft Windows XP Fujitsu Recovery (Hard Disk Based Recovery) Additional software (optional) DeskUpdate Driver management (puttonal with UMTS) Manageability DeskUpdate Driver management (April ** Pro** technology	is sector, options					
Runtime 1st battery Runtime 1st + 2nd battery Battery charging time -160 min (5,800 mAh) - 180 min (6,200 mAh) Battery notes Battery notes Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage. Rapid charge with 5,800 mAh batteries Dimensions / Weight / Environmental Dimensions (W x D x H) 372 x 245 x 35 mm Weight notes Incl. weight saver. Weight may vary depending on actual configuration. Operating ambient temperature 5 - 35°C Operating relative humidity 20 - 80 % Additional Software Additional Software (preinstalled) Adobe Acrobat Reader Application Panel Display Manager Shocksensor Utility Power Saving Utilities Off (DUDVO) UMTS connection manager (optional with UMTS) Manageability Manageability technology DeskUpdate Driver management IAMT 7.0 Intel® vPro™ technology	2nd battery (optional)					
Runtime 1st + 2nd battery Battery charging time Battery notes Battery notes Battery notes Battery Ilie may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage. Rapid charge with 5,800 mAh batteries Dimensions / Weight / Environmental Dimensions (W x D x H) 372 x 245 x 35 mm Weight notes Incl. weight saver. Weight may vary depending on actual configuration. Operating ambient temperature Operating ambient temperature 2 - 35°C Operating ambient temperature Operating relative humidity Additional Software Additional Software (preinstalled) Adobe Acrobat Reader Application Panel Display Manager ShockSensor Utility Power Saving Utilities DVD (DUDVD) Power Saving Utilities		•	,,			
Battery charging time Battery notes Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage. Rapid charge with 5,800 mAh batteries Dimensions / Weight / Environmental Dimensions (W x D x H) 372 x 245 x 35 mm Weight		· •				
Battery notes Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage. Rapid charge with 5,800 mAh batteries Dimensions (W x D x H) 372 x 245 x 35 mm Weight 2.5 kg Weight notes Incl. weight saver. Weight may vary depending on actual configuration. Operating ambient temperature Operating relative humidity 20 - 80 % Additional Software Additional Software (preinstalled) Adobe Acrobat Reader Application Panel Display Manager ShockSensor Utility Power Saving Utility Plugfree Network EasyGuide online user documentation Nero Essentials S (burning software) Additional software (optional) Drivers & Utilities DVD (DUDVD) UMTS connection manager (optional with UMTS) Manageability Manageability technology BeskUpdate Driver management Intel® vPro™ technology	·		0 min (6 200 mAh)			
Dimensions (W x D x H) 372 x 245 x 35 mm Weight 2.5 kg Weight notes Incl. weight saver. Weight may vary depending on actual configuration. Operating ambient temperature 5 - 35°C Operating relative humidity 20 - 80 % Additional Software Adobe Acrobat Reader Application Panel Display Manager ShockSensor Utility Power Saving Utility Plugfree Network EasyGuide online user documentation Nero Essentials S (burning software) Norton Internet Security (incl. Firewall) on Drivers & Utilities DVD for Microsoft Windows XP Figitsu Recovery (Hard Disk Based Recovery) Additional software (optional) Drivers & Utilities DVD (DUDVD) UMTS connection manager (optional with UMTS) Manageability DeskUpdate Driver management iAMT 7.0 Intel® vPro™ technology		Battery life may vary depend features utilized. Battery rech	ling on product model, configunarge time depends on usage		nanagement settings and	
Weight notes Incl. weight saver. Weight may vary depending on actual configuration. Operating ambient temperature 5 - 35°C Operating relative humidity 20 - 80 % Additional Software Adobe Acrobat Reader Application Panel Display Manager ShockSensor Utility Power Saving Utility Power Saving Utility Plugfree Network EasyGuide online user documentation Nero Essentials S (burning software) Norton Internet Security (incl. Firewall) on Drivers & Utilities DVD for Microsoft Windows XP Figitsu Recovery (Hard Disk Based Recovery) Additional software (optional) Drivers & Utilities DVD (DUDVD) UMTS connection manager (optional with UMTS) Manageability DeskUpdate Driver management iAMT 7.0 Intel® vPro™ technology	Dimensions / Weight / Environmental					
Weight notes Incl. weight saver. Weight may vary depending on actual configuration. Operating ambient temperature 5 - 35°C Operating relative humidity 20 - 80 % Additional Software Adobe Acrobat Reader Additional software (preinstalled) Adobe Acrobat Reader Application Panel Display Manager ShockSensor Utility Power Saving Utility Plugfree Network EasyGuide online user documentation Read Service Sesentials S (burning software) Norton Internet Security (incl. Firewall) on Drivers & Utilities DVD for Microsoft Windows XP Fujitsu Recovery (Hard Disk Based Recovery) Additional software (optional) Drivers & Utilities DVD (DUDVD) UMTS connection manager (optional with UMTS) Manageability DeskUpdate Driver management iAMT 7.0 Intel® vPro™ technology	Dimensions (W x D x H)	372 x 245 x 35 mm				
Operating ambient temperature Operating relative humidity 20 - 80 % Additional Software Additional software (preinstalled) Adobe Acrobat Reader Application Panel Display Manager ShockSensor Utility Power Saving Utility Plugfree Network EasyGuide online user documentation Nero Essentials S (burning software) Norton Internet Security (incl. Firewall) on Drivers & Utilities DVD for Microsoft Windows XP Fujitsu Recovery (Hard Disk Based Recovery) Additional software (optional) Drivers & Utilities DVD (DUDVD) UMTS connection manager (optional with UMTS) Manageability Manageability technology DeskUpdate Driver management iAMT 7.0 Intel® ∨Pro™ technology	Weight	2.5 kg				
Additional Software Additional software (preinstalled) Adobe Acrobat Reader Application Panel Display Manager ShockSensor Utility Power Saving Utility Plugfree Network EasyGuide online user documentation Nero Essentials S (burning software) Norton Internet Security (incl. Firewall) on Drivers & Utilities DVD for Microsoft Windows XP Fujitsu Recovery (Hard Disk Based Recovery) Additional software (optional) Drivers & Utilities DVD (DUDVD) UMTS connection manager (optional with UMTS) Manageability Manageability technology DeskUpdate Driver management iAMT 7.0 Intel® vPro™ technology	Weight notes	Incl. weight saver. Weight ma	ay vary depending on actual c	onfiguration.		
Additional Software (preinstalled) Adobe Acrobat Reader Application Panel Display Manager ShockSensor Utility Power Saving Utility Plugfree Network EasyGuide online user documentation Nero Essentials S (burning software) Norton Internet Security (incl. Firewall) on Drivers & Utilities DVD for Microsoft Windows XP Fujitsu Recovery (Hard Disk Based Recovery) Additional software (optional) Drivers & Utilities DVD (DUDVD) UMTS connection manager (optional with UMTS) Manageability Manageability technology DeskUpdate Driver management iAMT 7.0 Intel® vPro™ technology	Operating ambient temperature	5 - 35°C				
Additional software (preinstalled) Adobe Acrobat Reader Application Panel Display Manager ShockSensor Utility Power Saving Utility Plugfree Network EasyGuide online user documentation Nero Essentials S (burning software) Norton Internet Security (incl. Firewall) on Drivers & Utilities DVD for Microsoft Windows XP Fujitsu Recovery (Hard Disk Based Recovery) Additional software (optional) Drivers & Utilities DVD (DUDVD) UMTS connection manager (optional with UMTS) Manageability Manageability technology DeskUpdate Driver management iAMT 7.0 Intel® vPro™ technology	Operating relative humidity	20 - 80 %				
Additional software (preinstalled) Adobe Acrobat Reader Application Panel Display Manager ShockSensor Utility Power Saving Utility Plugfree Network EasyGuide online user documentation Nero Essentials S (burning software) Norton Internet Security (incl. Firewall) on Drivers & Utilities DVD for Microsoft Windows XP Fujitsu Recovery (Hard Disk Based Recovery) Additional software (optional) Drivers & Utilities DVD (DUDVD) UMTS connection manager (optional with UMTS) Manageability Manageability technology DeskUpdate Driver management iAMT 7.0 Intel® vPro™ technology	Additional Software					
UMTS connection manager (optional with UMTS) Manageability Manageability technology DeskUpdate Driver management iAMT 7.0 Intel® vPro™ technology		Application Panel Display Manager ShockSensor Utility Power Saving Utility Plugfree Network EasyGuide online user docum Nero Essentials S (burning so	oftware) I. Firewall) on Drivers & Utilitie	es DVD for Microsoft Windows :	ΧЪ	
Manageability technologyDeskUpdate Driver managementDeskUpdate Driver managementiAMT 7.0Intel® vPro™ technology	Additional software (optional)	Drivers & Utilities DVD (DUD)	/D)			
iAMT 7.0 Intel® vPro™ technology						
	Manageability technology	DeskUpdate Driver managen	nent	iAMT 7.0	nent	
	Manageability software	DeskView 10.x client manage	ement including:	J,		

Page 4 / 7 http://ts.fujitsu.com/mobile

Manageability	
DeskView components	BIOS Management
zezarien componento	DeskView Helpdesk Integration
	Detailed system inventory management and reports
	On/Offline remote client management
	Remote power management
	Security Remote Control
	System notifications
	WoL (Wake on LAN)
Supported standards	WMI
	PXE
	BootP (made4you)
Manageability link	http://ts.fujitsu.com/solutions/it_infrastructure_solutions/manageability/featurefinder.html
Security	
System protection	Kensington Lock support
Audit proof protection	Computrace® enabled BIOS
Addit proof protection	Optional: Trusted platform module (TPM 1.2)
	Norton Internet Security (incl. Firewall) 90 days version
Access protection	Hard disk password
Access protection	Integrated SmartCard slot
	User and supervisor BIOS password
	Optional: Integrated fingerprint sensor including Omnipass software
- "	optional. Integrated infigerprine sensor including offinipass software
Compliance	
Germany	GS .
Europe	CE Nordic Swan
Global	RoHS (Restriction of hazardous substances)
	WEEE (Waste electrical and electronic equipment)
	Microsoft Operating Systems (HCT / HCL entry / WHQL)
	WiFi certified
	ENERGY STAR® 5.0
	EPEAT® Silver (dedicated regions)
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx
Port Replicator interfaces (optional)	
DC-in	1 (19V)
Power on switch	1
Audio: headphone	1
Audio: microphone	1
USB 2.0 total	4
DisplayPort	1 (up to 2560 x 1600)
VGA	1
DVI	1 (up to 1920 x 1200)
	1 (up to 1320 x 1200)
Serial (RS-232)	<u>'</u>
Ethernet (RJ-45)	1 (10/100/1000)
Parallel	1
Kensington Lock support	1
eSATA	1
Notes	Port replicator does not support 0-Watt technology
Warranty	
Standard Warranty	1 year
Service level	Collect & Return Service / Bring-in Service (depending on country specific requirements)
Maintenance and Support Services - th	•
Recommended Service	5x9, Response Time: Next Business Day

Page 5 / 7 http://ts.fujitsu.com/mobile

١A	١.			_	ь.	١
Vν	и	п	и	ш	и١	

Spare Parts availability 5 years

Service Weblink http://ts.fujitsu.com/Supportservice

Recommended Accessories

Port Replicator



Flexibility, expandability, desktop replacement, investment protection to name just a few benefits of Fujitsu docking options.

Order Code: S26391-F987-L100

LIFEBOOK bundle (Port rep\AC Adapter\EU-Cable Kit)



Flexibility, expandability, desktop replacement to name just a few benefits Order Code: of Fujitsu docking options.

S26391-F987-L110

Order Code:

S26361-F1650-L900

2nd battery



power socket!

With a second battery you can maximize the working time of your notebook Order Code: and work wherever you want for a whole working day. Just put the 2nd S26391-F777-L200 battery into the modular bay and enjoy truly mobile working free from the

MicroSaver® Master Access DS, MicroSaver® DSMicrosaver® DS Ultra thin



Losing your notebook is unthinkable. Protect your computer with incomparable security, the disc lock. The most advanced disc locking technology is featured with carbon tempered steel core cable, external braided steel sheath, and patented T-Bar. This model offers the Master Access solution.The Kensington MicroSaver® DS Keyed Ultra-Thin Notebook Lock is designed for the ultimate defense of even the thinnest notebook. The nearly impenetrable disk style keyed locking mechanism along with an advanced cable design provides greater security.

Privacy filter



Privacy filters help block the screen view from anyone viewing the computer Order Code: from a side view. 3M's unique microlouver privacy technology allows S26391-F6097-L317 persons directly in front of the computer to see on-screen data clearly. 3M

Prestige Case Maxi 16



The Prestige Case Maxi 16 is designed to protect notebooks with up to 16-inch screens. The case features oversized pockets to provide storage for power adapters and is also equipped to hold business card and pens. The padded notebook compartment features shock-absorbing foam for added protection. The reinforced luggage strap makes it easy to attach the case to rolling luggage while traveling. The Prestige Case Maxi 16 features a professional design, ideal for the traveler who is looking for a functional business case.

offers the broadest line of computer filters available.

Order Code: S26391-F1191-L61

CELVIN® Drive D200



The CELVIN® Drive D200 is a highly reliable external storage device with marvelous USB 3.0 speed for Plug & Play experience by simply connecting the device to a notebook or PC. Furthermore it is easy to set up and increase the home network capacity by attaching it to the USB port of dedicated routers or NAS devices.

S26341-F103-L210

Order Code:

More information

Fujitsu platform solutions

In addition to Fujitsu LIFEBOOK E751, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu LIFEBOOK E751, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

http://ts.fujitsu.com/mobile

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT.

Please find further information at http://www.fujitsu.com/global/about/environment/



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see http://ts.fujitsu.com/terms_of_use.html Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

CONTACT

FUJITSU Technology Solutions Website: http://ts.fujitsu.com 2011-08-05 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions