



## AC1200 Dual Band Wireless USB Adapter TEW-805UB (v1.0R)

TRENDnet's AC1200 Dual Band Wireless USB Adapter, model TEW-805UB, connects a laptop or desktop computer to a revolutionary Wireless AC network. Connect to a Wireless AC network at an amazing 867 Mbps or to a Wireless N network at up to 300 Mbps. A SuperSpeed 5 Gbps USB 3.0 port maintains a high speed connection to your computer.

Quickly connect to a Wireless AC or N network at the touch of a button with the convenience of one-touch Wi-Fi Protected Setup (WPS). An LED on the front of the adapter conveys device status. Upgrade your computer's wireless connection to experience the speed of revolutionary Wireless AC.

**Wireless AC:** Next generation Wireless AC

**Dual Band:** Up to 867 Mbps Wireless AC or 300 Mbps Wireless N

**Compatible:** Connects to standard Wireless N networks

**USB 3.0:** SuperSpeed 5 Gbps USB 3.0 connection to computer

**Coverage:** Expanded coverage with MIMO technology

**One Touch Connection:** Connect to a router at the touch of the Wi-Fi Protected Setup (WPS) button

## PRODUCT OVERVIEW

- Upgrade your computer to revolutionary 867 Mbps Wireless AC
- Connect to a Wireless N network at up to 300 Mbps
- 5 Gbps USB 3.0 connection to computer
- Powered by the computer's USB port
- One-touch connection to router with Wi-Fi Protected Setup (WPS)

## FEATURES

- Wi-Fi compliant with IEEE 802.11ac and 802.11n standards
- High-speed data rates up to 867 Mbps with 802.11ac technology and 300 Mbps with 802.11n technology
- USB 3.0 connector
- LED indicator
- Backwards compatible with IEEE 802.11g, IEEE 802.11b, and IEEE 802.11a networks
- Compatible with Windows 8 (32/64-bit), 7 (32/64-bit), Vista (32/64-bit), and XP(32/64-bit) operating systems
- One-touch network connection with Wi-Fi Protected Setup (WPS) button
- Dynamic Data Rate Scaling from 867 Mbps to 1 Mbps
- Supports advanced wireless encryption up to WPA2-RADIUS
- Easy user setup and diagnostic utilities
- Coverage of up to 100 meters indoor (330 feet) and 300 meters outdoor (980 feet)\*
- 3-year limited warranty

\* Maximum wireless signal rates are referenced from IEEE 802.11 theoretical specifications. Actual data throughput and coverage will vary depending on interference, network traffic, building materials and other conditions.

## SPECIFICATIONS

### HARDWARE

<b>Interface</b>	<ul style="list-style-type: none"><li>• USB 3.0, 2.0, 1.1 standard</li></ul>
<b>Standards</b>	<ul style="list-style-type: none"><li>• IEEE 802.11a, IEEE 802.11ac (draft), IEEE 802.11b, IEEE 802.11g, and IEEE 802.11n</li></ul>
<b>WPS Button</b>	<ul style="list-style-type: none"><li>• Enables WPS connection</li></ul>
<b>Power Consumption</b>	<ul style="list-style-type: none"><li>• Receive mode: 167 mA (max.)</li><li>• Transmit mode: 224 mA (max)</li></ul>
<b>Supported OS</b>	<ul style="list-style-type: none"><li>• Windows 8 (32/64-bit), 7 (32/64-bit), Vista (32/64-bit), Windows XP (32/64-bit)</li></ul>
<b>Dimensions (L x W x H)</b>	<ul style="list-style-type: none"><li>• 80 x 27 x 12 mm (3.1 x 1 x 0.5 in.)</li></ul>
<b>Weight</b>	<ul style="list-style-type: none"><li>• 20 g (0.7 oz)</li></ul>
<b>Temperature</b>	<ul style="list-style-type: none"><li>• Operating: 0° ~ 40° C (32° ~ 104° F)</li><li>• Storage: -10° ~ 70° C (14° ~ 158° F)</li></ul>
<b>Humidity</b>	<ul style="list-style-type: none"><li>• Max 95% (non-condensing)</li></ul>
<b>Certifications</b>	<ul style="list-style-type: none"><li>• CE, FCC</li></ul>

### WIRELESS

<b>Modulation</b>	<ul style="list-style-type: none"><li>• DBPSK / DQPSK / CCK / OFDM (BPSK / QPSK / 16-QAM / 64-QAM / 128-QAM / 256-QAM)</li></ul>
<b>Antenna</b>	<ul style="list-style-type: none"><li>• 2 internal antennas</li></ul>
<b>Frequency</b>	<ul style="list-style-type: none"><li>• 802.11b/g/n: 2.412 ~ 2.472 GHz</li><li>• 802.11a/n/ac: 5.150 GHz ~ 5.350 GHz / 5.725 GHz ~ 5.825 GHz (FCC), 5.150 GHz ~ 5.350 GHz / 5.470 GHz ~ 5.725 GHz (ETSI)</li></ul>
<b>Media Access Protocol</b>	<ul style="list-style-type: none"><li>• CSMA/CA with ACK</li></ul>
<b>Data Rate (auto fallback)</b>	<ul style="list-style-type: none"><li>• 802.11a: up to 54 Mbps</li><li>• 802.11b: up to 11 Mbps</li><li>• 802.11g: up to 54 Mbps</li><li>• 802.11n: up to 300 Mbps (for both 2.4 &amp; 5 GHz)</li><li>• 802.11ac: up to 867 Mbps</li></ul>
<b>Output Power</b>	<ul style="list-style-type: none"><li>• 802.11b: 15 dBm (typical)</li><li>• 802.11g: 15 dBm (typical)</li><li>• 802.11n: 15 dBm (typical) (for both 2.4 &amp; 5 GHz)</li><li>• 802.11a: 15 dBm (typical)</li><li>• 802.11ac: 12 dBm (typical)</li></ul>
<b>Receiving Sensitivity</b>	<ul style="list-style-type: none"><li>• 802.11b: -76 dBm (typical)</li><li>• 802.11g: -65 dBm (typical)</li><li>• 802.11n: -61 dBm (typical)</li><li>• 802.11a: -65 dBm (typical)</li><li>• 802.11ac: -51 dBm (typical)</li></ul>
<b>Encryption</b>	<ul style="list-style-type: none"><li>• 64/128-bit WEP, WPA / WPA2-RADIUS, WPA / WPA2-PSK (AES/TKIP)</li></ul>
<b>Channels</b>	<ul style="list-style-type: none"><li>• 2.4 GHz: 1~11 (FCC), 1~13 (ETSI)</li><li>• 5 GHz: 36, 40, 44, 48, 52, 56, 60, 64, 149, 153, 157, 161, 165 (FCC) 36, 40, 44, 48, 52, 56, 60, 64, 100, 104, 108, 112, 116, 120, 124, 128, 132, 136, 140 (ETSI)</li></ul>


# AC1200 Dual Band Wireless USB Adapter

TEW-805UB (v1.0R)



## NETWORKING SOLUTIONS

### AC1200 Dual Band Wireless USB Adapter TEW-805UB



## PACKAGE CONTENTS

TEW-805UB

CD-ROM (Utility & Driver)

Multi-Language Quick Installation Guide

## RELATED PRODUCTS

TEW-812DRU AC1750 Dual Band Wireless Router

TEW-684UB N900 Dual Band Wireless USB Adapter

TEW-692GR N900 Dual Band Wireless Router

## CONTACT INFORMATION

**TRENDnet**

20675 Manhattan Place, Torrance, CA 90501 USA

Tel: 1-310-961-5500

Fax: 1-310-961-5511

Web: [www.trendnet.com](http://www.trendnet.com)

Email: [sales@trendnet.com](mailto:sales@trendnet.com)

**1-888-326-6061**

