



Offering a more flexible alternative to dot matrix technology, the GP-C831 combines the sturdiness of a dot matrix printer with the advantages of inkjet, such as wider media compatibility and higher-quality prints.

Unlike dot matrix printers, the versatile GP-C831 can print advanced barcodes, crisp text and photographs, and can be used with a variety of media, including glossy paper and labels. Whatever the media used, Epson's DURABrite Ultra pigment ink yields long-lasting prints that resist water, fading, smudging and highlighter pens.

The GP-C831 has a durable build and is designed to provide up to five years of high-volume, high-performance printing. Patented Epson technology protects the printhead nozzles from dust, making the GP-C831 suitable for demanding environments.

Helping to improve efficiency, the GP-C831 prints up to 19.7 pages per minute in super draft mode, and clears paper jams in seconds by automatically releasing the paper if an error occurs. This is backed up by a push-button manual paper release.

The GP-C831 comes with parallel, USB and LAN 100/10BASE interfaces as standard to make integration easy.

KEY FEATURES

- Prints on continuous paper
- Prints advanced barcodes
- Use with glossy and label media
- Long-lasting prints
- Anti-nozzle-block technology

PRODUCT SPECIFICATIONS

TECHNOLOGY

| | |
|----------------------|--|
| Printing Method | Epson Micro Piezo™ Serial inkjet printer |
| Nozzle Configuration | 360 Nozzles per colour |
| Colours | Black, Cyan, Yellow, Magenta |
| Ink Technology | Epson DURABrite™ Ultra |
| Category | Industrial colour label printer |

PRINT

| | |
|---------------------|------------------------|
| Printing Resolution | Max. 5,760 x 1,440 dpi |
| Printing Width | max. 2,032 mm |

SUPPORTED MEDIA

| | |
|---------|---------------------------------|
| Formats | Fanfold media with sprockets |
| Width | Min 762 mm, Max 2,413 mm |
| Type | Continuous paper, Die-cut label |

GENERAL

| | |
|------------------------|--|
| Interfaces | USB 2.0 Type A, Bidirectional parallel, Ethernet interface (100 Base-TX / 10 Base-T) |
| Power Supply | External |
| Supply voltage | 100 ~ 240 V, 50 ~ 60 Hz |
| Power consumption | Printing: Appx. 33 W, standby: Appx. 8 W |
| Temperature / humidity | Printing: 10~35 °C (20~80 % RH), Storage: -20~40 °C (5~85 % RH) |
| Product dimensions | 464 x 465 x 224 mm (Width x Depth x Height) |
| Product weight | 12.2 kg |

LOGISTICS INFORMATION

| | |
|--------------------------|--------------------|
| SKU | C11CC68132 |
| Barcode | 8715946530345 |
| Dimensions Single Carton | 680 x 589 x 424 mm |
| Carton Weight | 15.5 Kg |
| Multiple Order Quantity | 1 Units |
| Country of Origin | China |
| Pallet Size Euro | 40 Units (4 x 10) |
| Pallet Size Block | 60 Units (6 x 10) |

Epson GP-C831

WHAT'S IN THE BOX

- AC Adaptor
- Driver and utilities (CD)
- Main unit
- Setup guide
- User manual
- Individual Ink Cartridges

SUPPLIES

- GJIC5(C): Ink cartridge for GP-C831 (Cyan)
C13S020564
- GJIC5(M): Ink cartridge for GP-C831 (Magenta)
C13S020565
- GJIC5(Y): Ink cartridge for GP-C831 (Yellow)
C13S020566
- GJIC5(K): Ink cartridge for GP-C831 (Black)
C13S020563

For more information please contact:

Telephone: 0871 222 6702 (UK)+
01 436 7742 (Republic of Ireland)
E-mail: enquiries@epson.co.uk
Fax: 0871 222 6740

Web: www.epson.co.uk
www.epson.ie

+ Calls cost 10p per minute plus network extras.

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners.
Product information is subject to change without prior notice.

EPSON®