



ProLite XUB2390HS-B1

23" IPS monitor with ultra flat front and height adjustable stand

ProLite XUB2390HS is a 23" LED monitor with latest IPS Panel technology considered to be the best all round panel type. It offers accurate and consistent colour reproduction with wide viewing angles and a fast response time. A truly ergonomic stand including pivot function makes the XUB2390HS an excellent choice for photographic design, web design, standard office use. It's the perfect choice for multi-monitor applications.

DISPLAY CHARACTERISTICS

Diagonal	23"; 58.4cm
Panel	IPS LED
Display area h x w	286.4 x 509.2 mm; 11.3" x 20"
Response time	5 ms
Contrast	1000 : 1 typical
Contrast	5 000 000 : 1 ACR
Brightness	250 cd/m ² typical
Viewing zone	horizontal/vertical: 178° / 178°; right/left: 89° / 89°; up/down: 89° / 89°
Display colour	16.7 million
Pixel pitch h x v	0.265 x 0.265 mm
Native resolution	Full HD 1080p, 1920 x 1080 (2.1 megapixel)
Horizontal sync	24 - 80 KHz
Vertical sync	56 - 75 Hz
Synchronization	Separate sync
Aspect ratio	16 : 9

POWER MANAGEMENT

Power supply	AC100~240V 50/60Hz
Power Supply Unit	internal
Power usage	24 W typical; max. 0.5 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®

EU ENERGY EFFICIENCY LABEL

Energy efficiency class	A
On Mode Power Consumption	21.4W
Annual Energy Consumption	31 kW/annum*
Visible Screen Diagonal	51 cm; 23"

This is information under Regulation (EU) No 1062/2010.
*Based on the power consumption of the television operating 4 hours per day for 365 days. The actual energy consumption will depend on how the television is used.

EPEAT SILVER

EPEAT EPEAT is a comprehensive environmental rating that helps identify greener computers and other electronic equipment. The Silver certification means the monitor meets all required criteria plus at least 50% of the optional requirements. EPEAT Silver is valid in countries where iiyama registers the product. Please visit www.epeat.net for the registration status in your country.

INTERFACES & CONNECTORS

Analog input connector	VGA
Digital input connector	DVI-D, HDMI
HDCP	yes

SPECIAL FEATURES

Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Plug & Play	VESA DDC2B™
Controls	Via OSD in 9 languages (EN, DE, FR, ES, IT, PT, Chinese, RU, JP) and 5 front controls (Power, Menu, +/- Volume, +/- ECO, Auto)
Speakers	2 x 2 W (Stereo)
Anti-theft-device	Kensington-lock™ prepared
Certificates	TCO 6, CE, TÜV-Bauart, VCCI-B, CU
Height adjustment	130 mm
Rotation (pivot function)	90°
Swivel Stand	90°; 45° left; 45° right
Tilt angle	20° up; 4° down
VESA mounting	100 x 100 mm
Colour	Black

ACCESSORIES

Driver	Windows 95 / 98 / 2000 / ME / XP / Vista / 7 / 8
Included accessories	power cable, DVI-D cable, audio cable, stand, quick start guide, safety guide

DIMENSIONS & WEIGHT

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

Dimensions w x h x d	532.5 x 386 (516) x 230 mm
Weight	5.4 kg