

16 Port 1U Rack Mount USB KVM Switch Kit with OSD and Cables

StarTech ID: SV1631DUSBUK



The SV1631DUSBUK 16-Port Rack Mount USB KVM Switch Kit offers a well-appointed KVM switch that includes all of the cables and accessories required to connect to 16 servers or PCs right out of the box, making setup convenient and simple.

The USB KVM delivers a dependable computer management tool that allows you to control up to 16 USB-connected computers from a single keyboard, mouse and display, providing maximum control through hotkey command-based switching or front panel push-buttons, with the added configurability and convenience of an On-Screen Display.

A suitable addition to server room operations, the 16-port switch can be rackmounted into 1U of cabinet space and can be cascaded with multiple KVM switches to enable control of up to 136 computers from this single switch.

Applications and Solutions

- Systems management in Co-location/ISP facilities
- Central control for multiple systems in a Datacenter
- Manufacturing line computer control and management
- Great for PC test/burn-in computer control, avoiding the cost of buying additional peripherals
- Effectively manage your server farms from a single console





• Useful in Software QA labs where testing is being done across multiple platforms



Features

- Auto-scan function automatically switches between connected PCs sequentially
- Cascade configuration expands system capability
- Hotkey functions allow easy computer access
- Identifies and selects computers by the names assigned
- OSD security option allows selected KVM ports to be password-protected from unauthorized use
- Plug-and-play system configuration
- Rugged, all metal 1U chassis for use in harsh environments and server cabinets
- USB Keyboard and Mouse combo supported on 1 USB connection
- Package includes 16x 6ft USB KVM cables

Technical Specifications

Warranty: 3 Years
Product Depth: 180
Product Height: 45
Humidity: 0~80% RH

LED Indicators: Green - PC Online
LED Indicators: 1 - Green - Power
LED Indicators: Red - PC Selected
Maximum Cascaded Computers: 136

Maximum Analog Resolutions: 1920 x 1440@60Hz (1920 x 1200@60Hz - Wide Screen)

Maximum Number of Users: 1

Operating Temperature: 5°C to 40°C (41°F to 104°F)

• Output Current: 1000mA

• Carton Quantity: 1

• Storage Temperature: -20°C to 60°C (-4°F to 140°F)

Shipping (Package) Weight: 7.8 lb [3.53 kg]

• Product Weight: 31003100

• Product Width: 540

