Hanns·G

by **HANN**Spree



HS221HPB | EU

54,6cm / 21.5" Diagonal White LED-Backlight







- 1920 x 1080 WUXGA Resolution (54,6cm / 21.5" Diagonal)
- · LED Backlight Monitor
- ULTRA-WIDE VIEWING ANGLE
- Full HD 1080P
- 80,000,000:1 Active Contrast
- 5ms Response Time
- VGA+DVI+HDMI Compatible Inputs
- Multi-Video Modes : PC / Movie / Game / ECO
- Built-In Stereo Speakers
- Tilt and Wall-Mountable (VESA)
- Low Power Consumption































HS221HPB | EU

54,6cm / 21.5" Diagonal White LED-Backlight

| Har | ins:c | 5 |
|-----|------------------|---|
| by | HANN Spre | 2 |



| Physical | Kensington Lock | Yes | |
|------------------------------|-------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------|--|
| | VESA mounting | 100 x 100mm | |
| Controls | Front control | MENU ◀ ▶ AUTO 🖒 | |
| | On Screen Display | 12 language: EN, TC, DE, FR, ES, IT, PT, NL, SC, JS, KR, Russian | |
| | Preset Mode | PC, Movie, Game, ECO Modes | |
| Container Loading | 40' Standard | EU: 2100 | |
| | 20' Standard | EU:1000 | |
| Accessories | Power Cable(1.5m), VGA Cable(1.5m), Audio Cable(1.5m), User Manual (CD), Quick Start Guide (Paper) | | |
| Color Plan | Arm / Base /Bezel / Rear Cover - Texture | | |
| Carton box | Brown carton | | |
| Green product (Jan. 2009) | Yes | | |
| Window 8 | NA | | |
| Others | PC99 function(must) | | |
| Certification | CE, CB, EnergyStar6.x ,TCO6.0,GS | | |

Contact Information

Actual products may differ slightly from those illustrated on this promotion material. Please refer to actual samples for final selection. The products displayed on this promotion material may not be available for purchase in your particular country or locality. Please check with your local Hannspree authorized representatives for the availability of specific products in your area. Hannspree reserves the right to alter design and specifications as well as to change the accessories with equivalents without notice.

| LCD Panel | Display size | 54,6cm / 21.5" Diagonal White LED-Backlight |
|---------------------|-----------------------------------------------|--------------------------------------------------------------------|
| | Brightness | 250cd/m2 (Typical) |
| | Contrast | 1000:1 (Typical) 80,000,000:1 (Active Contrast) |
| | Pixel pitch | 0.248(H) x 0.248(V) |
| | Resolution (H x V) | 1920 x 1080 |
| | Aspect Ratio | 16:9 |
| | Response time | 5ms |
| | View angles LR,UD | H/V 178°/178°Ultra Wide Viewing Angle (IPS, ADS, PLStype of panel) |
| | Color | WARM,NATURE,COOL, User Mode |
| | Panel surface | Anti-glare |
| | Display colors | 16.7M Colors |
| PC Input Range | Horizontal Freq. | 30 to 83KHz |
| | Vertical Freq. | 56Hz to 75Hz |
| | Max. display frequency (Resolution H*V/Fv) | 1920 x 1080 /60 Hz |
| Interface | Input | D-Sub x 1, HDMI x1,PC Audio x1 ,DVI-D (HDCP) x1 |
| Output Terminal | Earphone | Yes |
| | Speaker | Yes |
| Power | Consumption | On: 30 W; Standby<=0.5W, Off<=0.5W |
| | AC Power Range | AC 100~240V, 50~60Hz |
| | Power Mode Indicator Light | Power on : Green (LED) Power saving : Green Flicker (LED) |
| Operating Condition | Temperature | 5°C ~ 35°C |
| | Humidity | 20% ~ 85%, non-condensing |
| Physical | Dimension (W*D*H) | 511 x 184 x 377mm |
| | Packing Dimension (W*D*H) | 563 x 101 x 428mm |
| | Net weight | 3.4Kg |
| | The margine | |
| | Gross weight | 4.5Kg |