

ThinkCentre M725 SFF 10VT000U++

Region EMEA	Speakers 1.5Wx1
Machine Type 10VT	Dust Filter None
TopSeller TopSeller	Stand None
Processor AMD Ryzen 3 PRO 2200G (4C, 3.5 / 3.6GHz, 2MB)	Keyboard / Mouse USB / USB
vPro No	Power Supply 180W 85%
Graphics Integrated AMD Radeon Vega 8 Graphics	Operating System Windows 10 Pro 64
Monitor Cable None	Warranty 1-year, Onsite
Memory 8GBx1	End of Support Aug 31, 2024
Storage 256GB SSD M.2 PCIe NVMe Opal	Ann Date (mm/yy) 07/18
Optical DVD±RW	
Media Reader None	
WLAN + Bluetooth None	
Ethernet Integrated	
Optional Front Ports None	
Optional Rear Ports None	
Chassis Intrusion Switch None	
Cable Lock None	



WWW.LENOVO.COM

This publication was developed for products and services offered in the United States and E.M.E.A countries. Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors.

Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.



<http://psref.lenovo.com>

Visit psref website for the latest version of Product Specifications Reference.

© Lenovo, 2017. All rights reserved.

Note:

* Country Code "US" is for United States, "++" is for EMEA countries (e.g. AD - Saudi, Arabia, AT - Austria, BM - Bulgaria, etc.), "xx" is for EAST countries (e.g. BM - Bulgaria, CX - Hungary, CY - Cyprus, etc.), and "***" is for MEA countries (e.g. AD - Saudi, Arabia, ED - Egypt, EQ - Sweden, etc.). Please be aware that the EMEA/ EAST/MEA models listed above might not be available in all countries

ThinkCentre M725 SFF Platform Specifications

Product Specifications Reference (PSREF)



Processor	AMD A6 / A8 / A10 / A12 and Ryzen 3 / 5 / 7 series processor						Manageability Security chip Security features	DASH 10/1.1 Discrete TPM 2.0, TCG Certified ● Security slot (in rear for optional Kensington® MicroSaver® cable) ● Padlock loop ● Smart USB protection, allows keyboard/mouse only, blocks all storage devices ● Optional cable lock to physically lock both keyboard and mouse ● Power-on password ● Administrator password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● Individual USB port disablement ● Optional chassis intrusion switch
	Processor	Cores / Threads	Frequency (Base/Max)	L2 Cache	Memory Support (Up to)	Integrated Graphics		
	PRO A6-9500	2 / 2	3.5 / 3.8	1MB	DDR4-2400	Radeon R5		
	PRO A8-9600	4 / 4	3.1 / 3.4	2MB	DDR4-2400	Radeon R7		
	PRO A10-9700	4 / 4	3.5 / 3.8	2MB	DDR4-2400	Radeon R7		
	PRO A12-9800	4 / 4	3.8 / 4.2	2MB	DDR4-2400	Radeon R7		
	Ryzen 3 2300X	4 / 4	3.5 / 4.0	2MB	DDR4-2933	None		
	Ryzen 5 2500X	4 / 8	3.6 / 4.0	2MB	DDR4-2933	None		
	Ryzen 3 PRO 2200G	4 / 4	3.5 / 3.6	2MB	DDR4-2933	Radeon Vega 8		
	Ryzen 5 PRO 2400G	4 / 8	3.6 / 3.8	2MB	DDR4-2933	Radeon RX Vega 11		
Ryzen 5 PRO 2600	6 / 12	3.4 / 3.9	3MB	DDR4-2933	None			
Ryzen 7 PRO 2700	8 / 16	3.2 / 4.1	4MB	DDR4-2933	None			
Memory	64GB max, UDIMM, DDR4-2666*, four 288-pin DIMM sockets, non-ECC, dual-channel capable * Systemboard supports up to DDR4-2666, memory frequency may automatically clocks down for the lower capability of memory controller in processor						Keyboard Some: Lenovo Calliope Keyboard (USB connector), black Some: Lenovo Traditional Keyboard (USB connector), black Some: Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black Some: Lenovo Keyboard (PS/2 connector), black (only available via special bid) Some: Lenovo Calliope Mouse (USB connector), black Some: Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black Some: Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black Some: Lenovo Mouse (PS/2 connector), black (only available via special bid)	
Storage	Some: Hard Drive / SATA 6.0Gb/s, 2.5" or 3.5", 5400 rpm or 7200 rpm Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Some: M.2 SSD / PCIe NVMe, PCIe 3.0 x 4*, 32Gb/s * 128GB SSD M.2 (2242) PCIe NVMe and AMD A6 / A8 / A10 / A12 processor only supports PCIe 3.0 x 2, 16Gb/s							
Optical	Some: DVD-ROM SATA 1.5Gb/s Drive, slim (9.0mm) Some: DVD Burner (DVD±RW), SATA 1.5Gb/s Drive, slim (9.0mm)							
Onboard SATA	Three onboard SATA 6.0Gb/s connectors, RAID 0/1 support (RAID preset only available via special bid model)							
Media reader	Optional 7-in-1 media reader							
Graphics	AMD Radeon™ Graphics in processor (only for some processors), uses main memory, DirectX® 12, one VGA, two DisplayPort™ (Onboard VGA and DP ports are only available on the models with integrated graphics), supports 3 independent displays, works along with AMD discrete graphics to support more displays; Max resolution: 4096x2160 (DP)@60Hz; 1920x1200 (VGA)@60Hz Some: NVIDIA GeForce® GT 730 , DirectX 12, 2GB GDDR5, PCIe 2.0 x16 (x8 elec.) adapter, two DisplayPort, 35 watts; Max resolution: 3840x2160 (DisplayPort)@60Hz							
Monitor cable	Optional DP to VGA dongle, DP to DVI-D dongle, DP to dual DP dongle, or DP to HDMI 1.4 dongle							
Chipset	AMD B450 Chipset							
Front ports (Std.)	2x USB 3.1 Gen2, 2x USB 3.1 Gen1, 1x microphone (3.5mm), 1x headphone (3.5mm)							
Front ports (Opt.)	Optional: 1x media reader, 2x USB 3.1 Type-C Gen2 via PCIe card (special bid only)							
Rear ports (Std.)	2x USB 3.1 Gen1, 2x USB 2.0, 1x serial (9-pin), 1x ethernet (RJ-45), 1x VGA*, 2x DisplayPort*, 2x PS/2 ports (keyboard / mouse); 1x line-in (3.5mm), 1x line-out (3.5mm), 1x microphone (3.5mm) * only available on the models with integrated graphics							
Rear ports (Opt.)	Optional: 2x USB 2.0, 1x 2nd serial (9-pin), 1x parallel (25-pin), additional RJ-45 and video ports available on optional graphics or ethernet card							
Audio support	High Definition (HD) Audio, Realtek ALC662 / optional internal speaker (1 watt)							
WLAN	Some: 11ac wireless, M.2 Card, Realtek RTL8821CE (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Qualcomm Atheros QCA9377A (dual band), Wi-Fi + Bluetooth 4.2* combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Realtek RTL8822BE (dual band), Wi-Fi + Bluetooth 4.2* combo adapter, 2x2 Some: 11ac wireless, M.2 Card, Qualcomm Atheros QCA6174A (dual band), Wi-Fi + Bluetooth 4.2* combo adapter, 2x2							
Bluetooth™	Some: Bluetooth 4.2* wireless, integrated in Wi-Fi + BT combo adapter * Hardware supports BT 4.2, but Win10 RS3 and earlier only supports BT 4.1							
Ethernet	Gigabit ethernet, Realtek RTL8111EPV, Wake on LAN®							
Ethernet (Opt.)	Some: Bitland BN8E88, gigabit ethernet, 1x RJ-45, PCIe x1 (special bid only)							
Manageability	DASH 10/1.1							
Security chip	Discrete TPM 2.0, TCG Certified							
Security features	● Security slot (in rear for optional Kensington® MicroSaver® cable) ● Padlock loop ● Smart USB protection, allows keyboard/mouse only, blocks all storage devices ● Optional cable lock to physically lock both keyboard and mouse ● Power-on password ● Administrator password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● Individual USB port disablement ● Optional chassis intrusion switch							
Keyboard	Some: Lenovo Calliope Keyboard (USB connector), black Some: Lenovo Traditional Keyboard (USB connector), black Some: Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black Some: Lenovo Keyboard (PS/2 connector), black (only available via special bid)							
Mouse	Some: Lenovo Calliope Mouse (USB connector), black Some: Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black Some: Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black Some: Lenovo Mouse (PS/2 connector), black (only available via special bid)							
Mechanical	● SFF (8.4L), black color; metal case ● (WxDxH) 3.6" X 11.4" X 13.5"; 92.5mm X 290.5mm X 343.5mm ● Approx. 13.2 lb (6.0 kg), weight may vary by configuration ● Toolless cover, disk, optical removal ● Optional dust filter Bay 1: Slim external ODD bay Bay 2: 3.5", internal, HDD/SSD Bay 3: 2.5", internal, HDD/SSD (bay only comes with 2.5" 2nd disk) Slot 1: low-profile (length < 150mm, height < 68mm), PCIe 3.0 x16 Slot 2: low-profile (length < 150mm, height < 68mm), PCIe 2.0 x1 Slot 3: low-profile (length < 150mm, height < 68mm), PCIe 2.0 x1 Slot 4: low-profile (length < 150mm, height < 68mm), PCI 3.0 M.2 card slots: two (one for WLAN, one for SSD)							
Floor Stand	Optional system floor stand for vertical orientation							
Power supply	Some: 180 watts, autosensing, 85% PSU Some: 210 watts, autosensing, 85% PSU Some: 260 watts, autosensing, 92% PSU (only available via special bid)							
Limited warranty	1-year or 3-year, limited onsite service / service upgrades available							
Preload	Preloaded operating system Some: Windows 10 Pro 64-bit Some: Windows 10 Home 64-bit Preloaded applications (only some listed) ● Lenovo Vantage ● Microsoft Office preloaded; purchase a product key to activate ● Cyberlink PowerDVD (only for models with DVD / DVD±RW) ● Cyberlink Power2GO (only for models with DVD±RW) ● LinkedIn							
Environment	ENERGY STAR® 6.1*, EPEAT™ Gold rating* (*not for non-OS models); ErP Lot 3; RoHS-compliant							
Accessories	For compatible accessories, please go to http://smartfind.lenovo.com							

Note: The specifications above may not be available in all regions.

Lenovo, July 2018

ThinkCentre M725 SFF

