ThinkCentre M725 SFF 10VT000V++

Region EMEA

Machine Type

10VT

TopSeller TopSeller

Processor

AMD Ryzen 5 PRO 2400G (4C, 3.6 / 3.8GHz, 2MB)

vPro No

Graphics

Integrated AMD Radeon RX Vega 11 Graphics

Monitor Cable

None

Memory 8GBx1

Storage

256GB SSD M.2 PCIe NVMe Opal

Optical DVD±RW

_ . _ _

Media Reader

None

WLAN + Bluetooth

None

Ethernet

Integrated

Optional Front Ports

None

Optional Rear Ports

None

Chassis Intrusion Switch

None

Cable Lock

None

Speakers

1.5Wx1

Dust Filter

Stand None

None

Keyboard / Mouse

USB / USB

Power Supply 180W 85%

Operating System

Windows 10 Pro 64

Warranty 1-year, Onsite

End of Support Aug 31, 2024

Ann Date (mm/yy)

07/18

Note:

Country Code "US" is for United States, "++" is for EMEA countries (e.g. AD - Saudi, Arabia, AT - Austria, BM - Bulgaria, etc.), "xx" is for EAST countries (e.g. BM - Bulgaria, CX - Hungary, CY - Cyprus, etc.), and "**" is for MEA countries (e.g. AD - Saudi, Arabia, ED - Egypt, EQ - Sweden, etc.). Please be aware that the EMEA/ EAST/MEA models listed above might not be available in all countries



www.lenovo.com

This publication was developed for products and services offered in the United States and E.M.E.A countries. Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area. Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or ftness for a particular purpose.



http://psref.lenovo.com

Visit psref website for the latest version of Product Specifications Reference.
© Lenovo, 2018. All rights reserved.





ThinkCentre M725 SFF Platform Specifications

Processor AMD A6 / A8 / A10 / A12 and Ryzen 3 / 5 / 7 series processor Manageability DASH 10/1.1										
Processor	Momory						Security chip Discrete TPM 2.0, TCG Certified			
	Processor	Cores / Threads	Frequency (Base/Max)	L2 Cache	Memory Support (Up to)	Integrated Graphics		Security slot (in rear for optional Kensington® MicroSaver® cable) Power-on password Administrator password		
	PRO A6-9500	2/2	3.5 / 3.8	1MB	DDR4-2400	Radeon R5			ock loop • Hard disk password	
	PRO A8-9600	4/4	3.1 / 3.4		DDR4-2400	Radeon R7			rt USB protection, allows keyboard/ • Boot sequence control	
	PRO A10-9700	4/4	3.5 / 3.8	2MB	DDR4-2400	Radeon R7			se only, blocks all storage devices Boot without keyboard and mouse	
	PRO A12-9800	4/4	3.8 / 4.2	+	DDR4-2400	Radeon R7			nal cable lock to physically lock keyboard and mouse • Individual USB port disablement • Optional chassis intrusion switch	
	Ryzen 3 2300X	4/4	3.5 / 4.0	+	DDR4-2933	None	Keyboard		Lenovo Calliope Keyboard (USB connector), black	
	Ryzen 5 2500X	4/8	3.6 / 4.0	+	DDR4-2933	None	Reyboard		Lenovo Traditional Keyboard (USB connector), black	
	Ryzen 3 PRO 2200G		3.5 / 3.6	+	DDR4-2933	Radeon Vega 8		Some:	Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black	
	Ryzen 5 PRO 2400G		3.6 / 3.8	+		Radeon RX Vega 11	Mouse	Some:	Lenovo Keyboard (PS/2 connector), black (only available via special bid)	
	Ryzen 5 PRO 2600	6/12	3.4 / 3.9	+	DDR4-2933	None	Mouse	Some:	Lenovo Calliope Mouse (USB connector), black Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black	
	Ryzen 7 PRO 2700	8/16	3.2 / 4.1	4MB	DDR4-2933	None		Some:	Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black	
Memory	64GB max, UDIMM,	DDR4-26	66*, four 288-	pin DIN	1M sockets, r	non-ECC,			Lenovo Mouse (PS/2 connector), black (only available via special bid)	
•	dual-channel capable						Mechanical	SFF (8.4L), black color; metal case		
	* System automatically clocks down for the processors with lower memory controlle							 (WxDxH) 3.6" X 11.4" X 13.5"; 92.5mm X 290.5mm X 343.5mm Approx. 13.2 lb (6.0 kg), weight may vary by configuration Toolless cover, disk, optical removal Optional dust filter 		
Storage	Some: Hard Drive / SATA 6.0Gb/s, 2.5" or 3.5", 5400 rpm or 7200 rpm									
	Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Some: M.2 SSD / PCIe NVMe, PCIe 3.0 x 4*, 32Gb/s									
	* 128GB SSD M.2 (2242) PCIe NVMe only supports PCIe 3.0 x 2, 16Gb/s								y 1: Slim external ODD bay	
Optical	Some: DVD-ROM S	SATA 1.5Gb/s Drive, slim (9.0mm)						Bay 2: 3	y 2: 3.5", nternal, HDD/SSD	
Onboard SATA	Some: DVD Burner (DVD±RW), SATA 1.5Gb/s Drive, slim (9.0mm) Three onboard SATA 6.0Gb/s connectors, RAID 0/1 support (RAID preset only						Bay 3: 2	y 3: 2.5", internal, HDD/SSD (bay only comes with 2.5" 2nd disk)		
Onboard SAIA	available via special			AID 0/ I	support (RA	nd preset only		Slot 2: 1	low-profile (length < 150mm, height < 68mm), PCIe 3.0 x16 low-profile (length < 150mm, height < 68mm), PCI 3.0	
Media reader	Optional 7-in-1 media reader							Slot 3: I	Slot 3: low-profile (length < 150mm, height < 68mm), PCI 3.0	
Graphics	AMD Radeon™ Graphics in processor (only for some processors), uses main							Slot 4: low-profile (length < 150mm, height < 68mm), PCIe 2.0 x1		
G. G	memory, DirectX® 12, one VGA, two DisplayPort™ (Onboard VGA and DP ports are only available on the models with integrated graphics), supports 3 independent displays, works along with AMD discrete graphics to support more displays; <i>Max resolution:</i> 4096x2160 (DP)@60Hz; 1920x1200 (VGA)@60Hz <i>Some:</i> NVIDIA Geforce® GT 730, DirectX 12, 2GB GDDR5, PCle 2.0 x16 adapter, one HDMI, one VGA, 35 watts; <i>Max resolution:</i> 3840x2160 (HDMI)@30Hz; 2048x1536 (VGA)@75Hz Optional DP to VGA dongle, DP to DVI-D dongle, DP to dual DP dongle, or DP to HDMI 1.4 dongle							M.2 card slots: two (one for WLAN, one for SSD)		
								Optional system floor stand for vertical orientation		
								Some: 180 watts, autosensing, 85% PSU Some: 210 watts, autosensing, 85% PSU Some: 260 watts, autosensing, 92% PSU (only available via special bid)		
							Librarita al communication			
Monitor poble							Limited warranty 1-year or 3-year, limited onsite service / service upgrades available			
Monitor cable							Preload	Preloaded operating system		
Chinaat							-	Some: Windows 10 Pro 64-bit Some: Windows 10 Home 64-bit		
Chipset	AMD B450 Chipset						_	Preloaded applications (only some listed) Lenovo Vantage Microsoft Office preloaded; purchase a product key to activate Cyberlink PowerDVD (only for models with DVD / DVD±RW) Cyberlink Power2GO (only for models with DVD±RW) LinkedIn		
Front ports (Std.)	2x USB 3.1 Gen2, 2x USB 3.1 Gen1, 1x microphone (3.5mm), 1x headphone									
Front ports (Opt.)	(3.5mm) Optional: 1x media reader, 2x USB 3.1 Type-C Gen2 via PCIe card (special bid only) 2x USB 3.1 Gen1, 2x USB 2.0, 1x serial (9-pin), 1x ethernet (RJ-45), 1x VGA*, 2x DisplayPort*, 2x PS/2 ports (keyboard / mouse); 1x line-in (3.5mm), 1x line-out (3.5mm), 1x microphone (3.5mm) * cply available on the models with integrated graphics.						\			
							′			
, ,										
Rear ports (Opt.)	* only available on the models with integrated graphics Optional: 2x USB 2.0, 1x 2nd serial (9-pin), 1x parallel (25-pin), additional RJ-45						Environment	ENERGY STAR® 6.1*, EPEAT™ Gold rating* (*not for non-OS models);		
(and video ports avail	able on or	otional graphi	cs or et	hernet card			ErP Lot	t 3; RoHS-compliant	
Audio support	High Definition (HD) Audio, Realtek ALC662 / optional internal speaker (1.5 watt)						Accessories	For con	npatible accessories, please go to http://smartfind.lenovo.com	
WLAN	Some: 11ac wireless, M.2 Card, Realtek RTL8821AE (dual band),									
	Wi-Fi + Bluetooth 4.2* combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Qualcomm Atheros QCA9377 (dual band), Wi-Fi + Bluetooth 4.2* combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Realtek RTL8822BE (dual band), Wi-Fi + Bluetooth 4.2* combo adapter, 2x2									
	Some: 11ac wireless, M.2 Card, Qualcomm Átheros QCA6174A (dual band), Wi-Fi + Bluetooth 4.2* combo adapter, 2x2									
Rluetooth™	Wi-Fi + Bluet Some: Bluetooth 4.2				L RT combo	adanter				
Bluetooth™	* Hardware supports	BT 4.2. h	s, integrated ii ut Win10 RS:	and ea	rlier only su	auaptei oports BT 4.1				
Ethernet	Gigabit ethernet, Rea	altek RTL8	3111EPV, Wa	ke on L	AN®					
Ethernet (Opt.)	Some: Bitland BN8E	88, gigabi	t ethernet, 1x	RJ-45,	PCle x1 (spe	ecial bid only)				











