

Dual Port Gigabit PCI Express Server Network Adapter Card - PCIe NIC

StarTech ID: ST1000SPEXD4



The ST1000SPEXD4 PCI Express Dual-Port Gigabit Network Card lets you add two gigabit Ethernet ports to a client, server or workstation through a single PCIe slot. Each port provides 10/100/1000 Mbps capable Ethernet and is fully compatible with IEEE 802.3/u/ab standards.

Suitable for any standard PCI Express-enabled system, the 2-port Ethernet card supports full-duplex flow control for maximum data transfer speeds of up to 2000 Mbps - an ideal 2-port NIC for setting up dual-homed, or multi-homed host configurations providing added security to corporate networks.

The dual-port server adapter is compliant with the PCIe 2.0 standard and features support for Jumbo Frames and 802.1q VLAN tagging as well as Wake on LAN (WoL). The adapter includes an optional low-profile / half-height bracket that can be used for installation into a standard or small form-factor computer chassis.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Applications

- Ideal for VM environments with multiple operating systems, requiring shared or dedicated NICs
- Provide redundant connectivity to ensure an uninterrupted network connection
- Configure a dual-homed proxy or gateway system for an added layer of security
- Specially designed for desktop PC clients, servers, and workstations with few PCI Express slots available

Features

- Two 10/100/1000Mbps compatible RJ-45 Ethernet ports
- Up to 9K Jumbo Frame support
- Compatible with PCI Express Base Specification 2.0 (backward compatible with 1.0a/1.1)
- Fully Compliant with IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, and supports IEEE 802.1Q VLAN tagging, IEEE 802.1P Layer 2 Priority Encoding and IEEE 802.3x Full Duplex Flow Control
- Supports Microsoft NDIS5 Checksum Offload (IP, TCP, UDP) and Large send Offload
- Wake-on-LAN / Remote Wake-up support
- Configured with standard profile bracket, low profile/half-height bracket included
- Supports Pair Swap / Polarity / Skew Correction

Technical Specifications

Warranty	2 Years
Ports	2
Interface	RJ45 (Gigabit Ethernet)
Bus Type	PCI Express
Card Type	Standard Profile (LP bracket incl.)
Port Style	Integrated on Card
Industry Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab
Industry Standards	PCI Express Base Specification 2.0
Chipset ID	Realtek - RTL8111E Asmedia - ASM1182E
Connector Type(s)	1 - PCI Express x1 Male
External Ports	2 - RJ-45 Female
Maximum Data Transfer Rate	2000 Mbps (full-duplex), 1000 Mbps (half-duplex)
Compatible Networks	10/100/1000 Mbps
Auto MDIX	Yes
Full Duplex Support	Yes
Jumbo Frame Support	9K max.
Supported Protocols	IEEE 802.1Q VLAN tagging, IEEE 802.1P Layer 2 Priority Encoding and IEEE 802.3x Full Duplex Flow Control
OS Compatibility	Windows® 8.1 / 8 (32/64bit), 7 (32/64), Vista(32/64), XP(32/64), 2000 Windows® Server 2012, 2008 R2, 2003(32/64) Mac OS 10.4 and up (Tested up to 10.10) Linux 2.4.x and up (Tested up to 3.5)
System and Cable Requirements	Available PCI Express slot
Product Length	92.6 mm [3.6 in]
Product Width	18 mm [0.7 in]
Product Height	120 mm [4.7 in]
Product Weight	54 g [1.9 oz]
LED Indicators	2 - Green - Link/Activity
LED Indicators	2 - Yellow - Gigabit Mode
Operating Temperature	0°C to 70°C (32°F to 158°F)
Storage Temperature	0°C to 100°C (32°F to 212°F)
Humidity	10~90% RH
Shipping (Package)	190 g [6.7 oz]

Weight

Included in Package	1 - PCIe Network Card
Included in Package	1 - Low Profile Bracket
Included in Package	1 - Driver CD
Included in Package	1 - Instruction Manual

Certifications, Reports and Compatibility

