

3 ft HDMI to VGA active converter cable – HDMI to VGA adapter – 1920x1200 or 1080p

StarTech ID: HD2VGAMM3



The HD2VGAMM3 3ft HDMI® to VGA converter cable lets you connect your HDMI equipped Chromebook™, laptop or desktop to a VGA monitor or projector, with no additional adapters or cables required.

The converter cable saves you the hassle of combining an HDMI to VGA adapter with a bulky VGA cable by providing an end-to-end solution for connecting your digital HDMI computer to your VGA monitor or projector.

Unlike most HDMI to VGA adapters which require a power outlet to convert the video signal, the HD2VGAMM3 doesn't need external power in most installations. To work with Mac computers where extra power is needed, the HD2VGAMM3 features an optional integrated USB power source (USB cable not included), which makes connecting a display to your desktop or workstation that much easier, if additional power is required.

In the past, converting digital HDMI to analog VGA was a difficult and expensive task. Now, you can avoid upgrade costs by connecting your HDMI video source to your existing VGA monitor or projector using the HD2VGAMM3. Plus, because the adapter cable supports video resolutions up to 1920x1200 or 1080p, you can rest assured you can use your existing VGA display while maintaining high-definition video quality.

The HD2VGAMM3 converter cable delivers a precise 3ft connection that eliminates the clutter of excess cable length and ensures a tidy, professional installation. For longer installations, we also offer a [6 ft HDMI to VGA cable \(HD2VGAMM6\)](#) and a [10 ft HDMI to VGA cable \(HD2VGAMM10\)](#), enabling you to choose the right cable length for your installation needs.

Please note: Digitally encrypted content from the HDMI video source will not be displayed.

The HD2VGAMM3 is backed by a 2-year StarTech.com warranty and free lifetime technical support.

Applications

Features

- Reduce clutter with a short 3ft adapter cable
- Avoid the hassle of additional adapters or cables with a built-in cable connecting an HDMI video source directly to a VGA monitor or projector
- Save upgrade costs by connecting your HDMI computer directly to a VGA monitor or projector
- Supports video resolutions up to 1920x1200 / 1080p
- Adapter and cable in one, with 1x male HDMI connector and 1x male VGA connector
- Plug-and-play installation

Technical Specifications

Warranty	2 Years
Converter Type	Active
Adapter Style	Cable Adapter
Audio	No
Chipset ID	Chrontel7101A
Output Signal	VGA
Connector Type(s)	1 - USB Micro-B (5 pin) Female
Connector A	1 - HDMI (19 pin) Male
Connector B	1 - VGA (15 pin; High Density D-Sub) Male
Maximum Cable Length	900 mm [35.4 in]
Maximum Analog Resolutions	1920 x 1200
Maximum Digital Resolutions	PC resolutions up to 1920 x 1200 @ 60 Hz
Cable Length	900 mm [35.4 in]
Product Length	900 mm [35.4 in]
Product Width	40 mm [1.6 in]
Product Height	15 mm [0.6 in]
Power Source	USB-Powered
Operating Temperature	0°C to 60°C (32°F to 140°F)
Storage Temperature	-10°C to 70°C (14°F to 158°F)
Humidity	40%-85%RH
Shipping (Package) Weight	0 kg [0 lb]

Certifications, Reports and Compatibility



Operating System
Independent

 **RoHS Compliant**
Available