

ThinkStation P330 SFF Platform Specifications

Product Specifications Reference (PSREF)

Components	Specification																								
Machine Type	MT 30C7 for Transactional model and MT 30C8 for Relationship model. For configuration of all 30C7 EMEA and US models, please visit: http://psref.lenovo.com/Product/ThinkStation/ThinkStation_P330_SFF																								
Form factor	8.4L mini-tower																								
Dimensions	Height: 343.5 mm (13.5 in). Width: 92.5 mm (3.6 in). Depth: 305.6 mm (12 in)																								
Weight	Maximum configuration: 13.23 lb (6.0kg)																								
Processor	Up to one Intel Xeon E-2100 family processor, up to 80W, up to 6 cores at 3.7GHz, up to 3.8GHz with 4 cores, up to 12MB cache, DDR4-2666 memory speed. Or up to one 8th Intel Core family processor, i7, i5, or i3, up to 65W, up to 6 cores at 3.2GHz, up to 3.7GHz with 4 cores, up to 12MB cache, up to DDR4-2666 memory speed. Or up to one Intel Pentium G5400 via Special Bids, 58W, 2 cores at 3.7GHz, 4MB cache, DDR4-2400 memory speed																								
Chipset	Intel C246 Chipset																								
Memory	4 DIMM sockets. DDR4-2666. UDIMM. ECC and non-ECC are supported, but memory types cannot be intermixed																								
Memory capacity	Up to 64GB with 4x 16GB, both ECC and non-ECC																								
Memory protection	ECC with ECC UDIMM. Core i7 and i5 processors cannot support ECC UDIMM																								
Expansion slots	Three PCIe 3.0 slots as following:																								
	Slot 1 PCIe 3.0 x16, full height, half length, links to CPU																								
	Slot 2 PCIe 3.0 x1, full height, full length, links to PCH																								
Graphics - Processor graphics	Integrated Intel UHD Graphics P630 in -G suffix Xeon processors, or Intel UHD Graphics 630 in Core i7, i5, or i3 processors, or Intel UHD Graphics 610 in Pentium Gold G5400. Works along with discrete graphics to support multi-display, enables three display connectors (2x DP, 1x HDMI. HDMI is optional) on rear																								
	Up to two PCIe 3.0 x16 slots for discrete graphics adapter (Slot 1 and 3). Supports the following graphics adapters:																								
Graphics - Discrete graphics card	<table border="1"> <thead> <tr> <th>Adapter</th> <th>Cores</th> <th>Memory</th> <th>Power</th> <th>Connectors</th> <th>Max qty</th> </tr> </thead> <tbody> <tr> <td>Quadro P400</td> <td>256</td> <td>2GB GDDR5</td> <td>30W</td> <td>3x miniDP</td> <td>2</td> </tr> <tr> <td>Quadro P620</td> <td>512</td> <td>2GB GDDR5</td> <td>40W</td> <td>4x miniDP</td> <td>2</td> </tr> <tr> <td>Quadro P1000</td> <td>640</td> <td>4GB GDDR5</td> <td>47W</td> <td>4x miniDP</td> <td>2</td> </tr> </tbody> </table>	Adapter	Cores	Memory	Power	Connectors	Max qty	Quadro P400	256	2GB GDDR5	30W	3x miniDP	2	Quadro P620	512	2GB GDDR5	40W	4x miniDP	2	Quadro P1000	640	4GB GDDR5	47W	4x miniDP	2
	Adapter	Cores	Memory	Power	Connectors	Max qty																			
	Quadro P400	256	2GB GDDR5	30W	3x miniDP	2																			
	Quadro P620	512	2GB GDDR5	40W	4x miniDP	2																			
Quadro P1000	640	4GB GDDR5	47W	4x miniDP	2																				
Storage controllers	Integrated Intel SATA AHCI/RAID controller in chipset, 6Gbps SATA, RAID 0/1. Four onboard SATA ports for max 4 SATA HDD/SSD/ODD																								
Internal storage bay	Up to 3 bays with two disk bays and one slim optical bay:																								
	Bay 1 Primary 3.5" SATA bay																								
	Bay 2 2.5" SATA bay																								
Disks	3.5" HDD supports up to 4TB each, 6Gbps SATA, 7.2K. 2.5" SSD supports up to 1TB each, 6Gbps SATA																								
	Up to 3x M.2 SSD with one dedicated onboard M.2 slot plus two PCIe to M.2 adapters. PCIe to M.2 adapter uses slot 1 or 3. Supports RAID 0/1 with PCH, When used as RAID, M.2 SSD should be installed in onboard M.2 slot and slot 3. Up to one Optane memory per system; Optane memory must work with a HDD or SSD; Optane memory cannot supported on Pentium G5400 models																								
M.2 slot for SSD	M.2 SSD supports up to 1TB each, PCIe 3.0 x4, NVMe, Opal. Optane memory supports 32GB, PCIe 3.0 x2, NVMe, 3D Xpoint																								
M.2 slot for Wi-Fi and Bluetooth	One dedicated onboard M.2 slot for optional Intel Wireless-AC 9560, 2x2, 2.4GHz/5GHz (160MHz channels), 802.11ac, Bluetooth 5, up to 1.73Gbps																								

Components	Specification
Media reader	Optional SD card reader on most models
Network interfaces	One onboard GbE port via integrated gigabit ethernet Intel i219LM, supports Wake-on-LAN. Optional PCIe ethernet adapters are available
Security features	Power-on and admin password. Trusted Platform Module, TCG 2.0 compliant. Optional chassis intrusion switch, cable lock, Kensington lock, and pad lock
Systems management	Intel Active Management Technology 12 on Xeon models, Intel Standard Manageability on other models
Base warranty	US models comes with 3-year limited onsite service with 9x5/NBD. 1 or 3-year limited onsite service with 9x5/NBD in EMEA or other GEOs
HD Audio	Intel HD Audio interface with Realtek ALC233 Codec
Front ports	2x USB 3.1 Gen 1 Type A. 2x USB 3.1 Gen 2 Type A. 1x USB 3.1 Gen 1 Type-C. 1x Mic-in. 1x Combo jack
Rear ports	2x USB 3.1 Gen 1 Type A. 2x USB 2.0 Type-A. 1x RJ-45. 1x COM. 2x DP. <i>Notes: DP needs Core, Pentium, or -G suffix Xeon processor</i>
Optional rear ports	2x USB 3.1 Type-C. 1x COM. PS/2. 1x Parallel. 1x Thunderbolt. 1x IEEE1394. 1x HDMI. <i>Notes: HDMI needs Core, Pentium, or -G suffix Xeon processor</i>
Temperature	Operating: 41 °F to 104 °F (10 °C to 35 °C)
	Non operating (no package): 14 °F to 140 °F (-10 °C to 60 °C)
	Non operating (with package): -40 °F to 140 °F (-40 °C to 60 °C)
Altitude	Operating: -15.2 m (-50 ft) to 3048 m (10 000 ft).
	Storage: -15.2 m (-50 ft) to 10, 668 m (35 000 ft)
Humidity	Operating: 30%-90%, non-condensing
	Storage (with package): 20%-90%, non-condensing
Environmental certification	RoHS-compliant. GREENGUARD. EPEAT Gold rating and ENERGY STAR 7 qualified
Power supply	Supports one 210W or 260W power supply. 210W is 100V - 240V, 85% PSU, Climate Savers Computing Bronze and 80 PLUS Bronze qualified.
	260W is 100V - 240V, 92% PSU, Climate Savers Computing Platinum and 80 PLUS Platinum qualified
ISV certifications	Please visit www.thinkworkstations.com/isv-certifications/

