



Hi-Speed USB 2.0 Active Extension Cable

Daisy-Chainable, A Male / A Female, 10 m (33 ft.)

Model
150248

Easily overcome distance limitations to connect USB devices.

Use the MANHATTAN® Hi-Speed USB 2.0 Active Cable to connect a computer USB port to a USB device almost anywhere in the room. Up to three daisy-chainable cable extensions provides a convenient, 15 m (50 ft.) connection.

Meets USB Standards

MANHATTAN Hi-Speed USB 2.0 Active Cable with built-in repeater is fully compliant with USB 1.1 and Hi-Speed USB 2.0 specifications to help devices operate at maximum performance levels.

Quick and Easy Installation


Plug and Play capability, Windows/Macintosh versatility and no external power or driver requirements help provide greater flexibility in computer and peripheral placement and office layout.

Lifetime Warranty

Strict manufacturing standards ensure the highest quality in all MANHATTAN products. All items carry a full Lifetime Warranty — the strongest quality commitment anyone can make.



REV	DATE	REV JIMENSIS	DESIGN	CHECK	APPROVE
1	01-04-12	REV DRAWING	lyh		



Electronic Test:

1. Contact Resistance : 20mΩ max
2. Insulation Resistance : 10M ohm min
3. Hi-Pot : 300V DC/10ms
4. All Materials With RoHS Standard

Material List:

NO.	NAME	DESCRIPTION	UNIT	Q'TY
1	CABLE	USB-A 28AWG *19#*22AWG*28 Double Shield Jacket Color:transparence brown OD:4.7	m	10000
2	CONNECTOR	USB (A) male Solder Type Insulation Color:White Pin Gold Plated Terminal:Shell Gold Plated	set	1
3	CONNECTOR	USB (A) female Solder Type Insulation Color:White Pin Gold Plated Terminal:Shell Nickel Plated	set	1
4	INSIDE MOLDING	LD PE	g	5
5	OUTSIDE MOLDING	30P PVC CLEAR (transparence brown)	g	12
6	TUBE	OD:0.4 L:5mm	PCS	1
7	PCI	PCB	PCS	1

Pin Assignment

Conn. 1	Conn. 2
1	1 Red
2	2 White
3	3 Green
4	4 Black
5	Shell

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF MANHATTAN AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF MANHATTAN.

CUSTOMER:

DWG NO.:

ITEM NO.:

MANHATTAN



SCALE: NONE

DRAWN BY: lyh

PART NO.:

UNIT: mm

CHECKED BY:

REV:A

APPROVED BY:

Features

- Extends and boosts the signal to any USB device – supports data transfer speeds up to 480 Mbps
- Built-in repeater helps maintain Hi-Speed USB 2.0 signal quality, electrical and timing specifications
- Overcomes the 5 m (16 ft.) USB distance limitation – ideal for connecting enclosures and other peripherals
- Daisy-chain up to three extensions for a total distance of 30 m (99 ft.)
- Plug and Play; Windows and Mac compatible; bus-powered – requires no external power supply
- Lifetime Warranty

Specifications

STANDARDS AND CERTIFICATIONS

- CE
- FCC
- USB 1.0
- USB 1.1
- USB 2.0

PORTS

- A-type male
- A-type female

GENERAL

- Throughput: 480 Mbps
- Bus powered
- Max. length: 30 m (99 ft.)
- All USB-supported operating systems

PHYSICAL

- LENGTH: 10 M (33 FT.)
- WEIGHT: 314 G (11.1 OZ.)

PACKAGE CONTENTS

- Hi-Speed USB 2.0 Active Cable

For more information on MANHATTAN products, consult your local dealer or visit www.manhattan-products.com.

MANHATTAN
BRINGING COMPUTERS TO LIFE

Copyright © MANHATTAN

